

Elektroniikan suunnittelukeskuksen varastokomponentit

Keraamiset kondensaattorit 0805

| CompID | Arvo | Jännitekesto | Käyttölämpötila (°C) | Toleranssi | TC | Eriste |
|--------|--------|--------------|----------------------|------------|-------------|--------|
| 11400 | 1 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11401 | 1,2 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11402 | 1,5 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11403 | 1,8 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11404 | 2,2 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11405 | 2,7 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11406 | 3,3 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11407 | 3,9 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11408 | 4,7 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11409 | 5,6 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11410 | 6,8 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11411 | 8,2 pF | 50 V | -55...+125 | ± 0,5 pF | ± 30 ppm/°C | NPO |
| 11412 | 10 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11413 | 12 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11414 | 15 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11415 | 18 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11416 | 22 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11417 | 27 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11418 | 33 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11419 | 39 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11420 | 47 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11421 | 56 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11422 | 68 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11423 | 82 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11424 | 100 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11425 | 120 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11426 | 150 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11427 | 180 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11428 | 220 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11440 | 220 pF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11429 | 270 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11441 | 270 pF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11430 | 330 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11442 | 330 pF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11431 | 390 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11443 | 390 pF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |

Elektroniikan suunnittelukeskus ei vastaa taulukkojen mahdollisesti sisältämistä virheistä

Keraamiset kondensaattorit 0805

| CompID | Arvo | Jännitekesto | Käyttölämpötila (°C) | Toleranssi | TC | Eriste |
|--------|--------|--------------|----------------------|------------|-------------|--------|
| 11432 | 470 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11444 | 470 pF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11433 | 560 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11445 | 560 pF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11434 | 680 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11446 | 680 pF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11435 | 820 pF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11447 | 820 pF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11436 | 1 nF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11448 | 1 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11437 | 1,2 nF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11449 | 1,2 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11438 | 1,5 nF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11450 | 1,5 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11439 | 1,8 nF | 50 V | -55...+125 | ± 5 % | ± 30 ppm/°C | NPO |
| 11451 | 1,8 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11452 | 2,2 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11453 | 2,7 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11454 | 3,3 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11455 | 3,9 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11456 | 4,7 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11457 | 5,6 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11458 | 6,8 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11459 | 8,2 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11460 | 10 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11461 | 12 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11462 | 15 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11463 | 18 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11464 | 22 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11465 | 27 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11466 | 33 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11467 | 39 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11468 | 47 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11469 | 56 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11470 | 68 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11471 | 82 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |
| 11472 | 100 nF | 50 V | -55...+125 | ± 10 % | ± 15 % | X7R |